


LED LIGHTING INDOOR

LUMITENSO ECO LED TUBE T8 60

LUMITENSO ECO LED tubes are among the most efficient LED tubes on the market. High-performance thermal management ensures low heat generation along with maximum lighting intensity. Whether in office buildings, public buildings or private homes, LUMITENSO LED tubes provide reliable, environmentally-friendly lighting without compromising on quality, brightness, design or comfort.



- High-quality thermal management with low heat generation
- High shock and vibration resistance
- Five-year product warranty
- Low maintenance costs
- Long-lasting
- Reduced CO2 emissions
- Mercury-free

LUMITENSO ECO LED TUBES

LUMITENSO PRODUCT FAMILY: EFFICIENT LIGHTING FOR ALL AREAS











TECHNICAL DATA LUMITENSO ECO LED TUBE T8 60

TYPE DESIGNATION				
Model name	LUMITENSO ECO LED tube T8 milky			
Article no.	875067	875074	875081	
Color temperature*	3,000 K/ww	4,000 K/nw	6,000 K/dl	
Lumen	900 lm	1,000 lm	1,050 lm	
Light output	90 lm/W	100 lm/W	105 lm/W	
Color Rendering Index (CRI)	≥80	≥80	≥80	
Consumption	10 W			
Cover	milky			
Dimensions	ø 26 x 600 mm (ø without end cap)			

^{*}ww (warm white), nw (neutral white), dl (daylight)

GENERAL		
IP class	IP20	
Weight	180 g	
Socket	G13	
Beam angle	120°	
Dimmable yes/no	no	
Electrical connection	AC100-240V/50-60Hz	
Powerfactor	≥ 0.9	
Warranty	60 months	

LIMITS	
Operating temperature	-20 ~ 45 °C
Lifetime	50,000 h

FIELDS OF APPLICATION

Indoor

LUMITENSO ECO LED tubes are suitable for use indoors: office buildings, practices, schools, etc.

Subject to technical alterations; errors and misprints excepted. The general terms and conditions as well as the product and performance warranties of Lumitenso GmbH apply. Status as of $o_3/2014$










CERTIFICATES/STANDARDS	
Standards	ISO 9001; ISO 14001; RoHS 2011/65/EU; LVD 2006/95/EC; EMC 2004/108/EC; TÜV
Conformity	CE-compliant

LIGHT DISTRIBUTION CURVE		
Tube T8 60	4,000 K	cd/ 1,000 lm





LED Light, that's Worth It

