
LED LIGHTING INDOOR

LUMITENSO ECO LED PANEL 60x60

LUMITENSO ECO LED panels combine the latest technical expertise with cutting-edge design. The system solution represents the ideal alternative to standard grid lighting fixtures. Whether in office buildings, public buildings or private homes, LUMITENSO LED panels provide reliable, environmentally-friendly lighting without compromising on quality, brightness, design or comfort.



- Up to 80 % savings on energy costs
- High-quality thermal management with low heat generation
- Patented control technology
- High shock and vibration resistance
- Three-year product warranty
- Low maintenance costs
- Long-lasting
- Reduced CO2 emissions
- Mercury-free

LUMITENSO ECO LED PANELS





LUMITENSO PRODUCT FAMILY: EFFICIENT LIGHTING FOR ALL AREAS











TECHNICAL DATA

TYPE DESIGNATION						
Model name	LUMITENSO ECO LED panel 59 x 59 Box			LUMITENSO ECO LED panel 62x62 Bo2		
Article no.	875159	875166	875173	875210	875227	875234
Color temperature	3,000 K	4,000 K	6,000 K	3,000 K	4,000 K	6,000 K
Lumen	2,800 lm	3,100 lm	3,200 lm	2,800 lm	3,000 lm	3,300 lm
Color Rendering Index (CRI)	≥80	≥80	≥80	≥80	≥80	≥80
Consumption	42 W			42 W		
Cover	milky			milky		
Dimensions	595 x 595 x 40 mm (hole size 580 x 580 mm)			622 x 622 x 50 mm (hole size 607 x 607 mm)		

GENERAL	
IP class	IP20
Weight	2,850 g
Type / socket	LED panel
Beam angle	110°
Dimmable yes/no	no
Electrical connection	AC 100-240 V /50-60 Hz
Powerfactor	≥ 0.9
Warranty	36 months

LIMITS	
Operating temperature	-30 ~ 50 °C
Lifetime	35,000 h (at 25°C)

CERTIFICATES/STANDARDS	
Standards	ISO 9001; ISO 14001;
	RoHS 2011/65/EU;
	LVD 2006/95/EC;
	EMC 2004/108/EC
Conformity	CE-compliant

FIELDS OF APPLICATION

Indoor

LUMITENSO ECO LED panels are suitable for use indoors: office buildings, practices, schools, etc.

Subject to technical alterations; errors and misprints excepted. The general terms and conditions as well as the product and performance warranties of SiG Solar LUX GmbH apply. Status as of 09/2013









